

NovoTouch

LK9810i



Model Name	NovoTouch LK9810i
Display Technology	Backlit LED (IPS Panel)
Panel Size; Aspect Ratio	98", 16:9
Brightness	440cd/m2
Contrast Ratio (Typical)	1,300:1
Native Resolution	4K Ultra-HD (3840 x 2160)
Viewing Angle (Horiz/Vert)	178°/178°
Refresh Rate (Hz)	120Hz
Display Color (Bit)	1.06 billion (10-bit)
Orientation	Landscape
Touch Technology	Infrared Touch
Touch Points	5 Writing, 10 Touch
Surface Protection	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
Minimum Touch Object	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm
Touch Tools	Finger, Stylus, Glove, Opaque Objects
Gestures Supported	Yes
System Version	Android™ v4.2.1
CPU	ARM® Cortex® A9 Dual Core CPU
GPU	Quad Core GPU
RAM	1.5G RAM
Internal Storage	8GB
OS Compatibility	Windows® (Windows 7 and above: Driver Free), Mac® (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernel v3.5 and above)
I/O Ports	HDMI v1.4 (x1), HDMI v1.3 (x3), AV-In (x1), VGA-In (x3), Audio-In (x3), VGA-Out (x1), Audio-Out (3.5mm (x1)), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB 3.0 (x1), USB Type B (x2)
Internal Speakers	10W (x2) (Stereo)
Power	AC 100-240V, 50/60Hz. Consumption: 650W, <0.5W (Standby)
Panel Dimensions	2,257 x 1,335 x 121 mm
Panel Weight (Net)	150 kg
Panel Weight (Gross)	200 kg
What's included	Touch Screen Panel, NovoEnterprise NE3000EU, Wall Mount WIB9060A, Documentation Kit, AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control with Batteries.