

Specifications	NovoTouch LK6530i	NovoTouch LK7530i	NovoTouch LK8630i
Display Technology	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)
Panel Size; Aspect Ratio	65", 16:9	75", 16:9	86", 16:9
Brightness	350cd/m²	330cd/m²	330cd/m²
Contrast Ratio (Typical)	1,200:1	1,200:1	1,200:1
Native Resolution	4K Ultra-HD (3840 x 2160)		
Viewing Angle (Horiz/Vert)	178°/178°		
Refresh Rate (Hz)	60Hz	60Hz	60Hz
Display Color (Bit)	1.06 billion (10-bit)		
Orientation	Landscape		
Touch Technology	Infrared Touch		
Touch Points	10 Writing, 20 Touch	10 Writing, 20 Touch	10 Writing, 20 Touch
Surface Protection	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)		
Minimum Touch Object	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm		
Touch Tools	Finger, Stylus, Glove, Opaque Objects		
Gestures Supported	Yes		
System Version	Android™ v6.0	Android™ v6.0	Android™ v6.0
CPU	RK3399, Dual-Core ARM® Cortex® A72 and Quad Core ARM® Cortex® A53		
GPU	Mali™ T860	Mali™ T860	Mali™ T860
RAM	4GB DDR3	4GB DDR3	4GB DDR3
Internal Storage	16GB	16GB	16GB
OS Compatibility	Windows® (Windows 7 and above: Driver Free), macOS (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernal v3.5 and above)		
I/O Ports	HDMI v2 (x1), HDMI v1.4 (x2), DisplayPort (x1), VGA-In (x1), Audio-In (3.5mm) (x1), AV-In (x1), HDMI-Out (1080P) (x1), Audio-Out (3.5mm) (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB Type A 3.0 (x2), USB Type B (x2)		
Internal Speakers	12W (x2) (Stereo)	12W (x2) (Stereo)	12W (x2) (Stereo)
Power Supply (Internal)	AC 100-240V, 50/60Hz		
Dimensions	1,521 x 915 x 99 mm	1,762 x 1,034 x 101 mm	1,988 x 1,178 x 99.6 mm
Weight (Net)	46 kg	60 kg	78 kg
Weight (Gross)	60.4 kg	84.2 kg	111.2 kg
Accessories (Standard)	AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control, Wall Mount Kit, Documentation Kit		