

Specifications	NovoTouch LK6530i	NovoTouch LK7530i	NovoTouch LK8630i	NovoTouch LK9820i
Display Technology	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)
Panel Size; Aspect Ratio	65", 16:9	75", 16:9	86", 16:9	98", 16:9
Brightness	350cd/m ²	330cd/m ²	330cd/m ²	500cd/m ²
Contrast Ratio (Typical)	1,200:1	1,200:1	1,200:1	1,300:1
Native Resolution	4K Ultra-HD (3840 x 2160)			
Viewing Angle (Horiz/Vert)	178°/178°			
Refresh Rate (Hz)	60Hz	60Hz	60Hz	120Hz
Display Color (Bit)	1.06 billion (10-bit)			
Orientation	Landscape			
Touch Technology	Infrared Touch			
Touch Points	10 Writing, 20 Touch	10 Writing, 20 Touch	10 Writing, 20 Touch	10 Writing, 10 Touch
Surface Protection	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)			
Minimum Touch Object	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm			
Touch Tools	Finger, Stylus, Glove, Opaque Objects			
Gestures Supported	Yes			
System Version	Android™ v6.0	Android™ v6.0	Android™ v6.0	Android™ v5.0
CPU	RK3399, Dual-Core ARM® Cortex® A72 and Quad Core ARM® Cortex® A53			Quad Core ARM Cortex A53 CPU - Up to 1.4GHz
GPU	Mali™ T860	Mali™ T860	Mali™ T860	Mali™- 450
RAM	4GB DDR3	4GB DDR3	4GB DDR3	2GB DDR3
Internal Storage	16GB	16GB	16GB	16GB
OS Compatibility	Windows (Windows 7 and above: Driver Free), macOS (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernel v3.5 and above)			
I/O Ports	HDMI v2 (x1), HDMI v1.4 (x2), DisplayPort (x1), VGA-In (x1), Audio-In (3.5mm) (x1), AV-In (x1), HDMI-Out (1080P) (x1), Audio-Out (3.5mm) (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB Type A 3.0 (x2), USB Type B (x2)			HDMI v2 (x4), HDMI v1.4 (x1), VGA-In (x1), YPbPr-In (x1), AV-In (x1), Audio-In 3.5mm (x1), Microphone-In 3.5mm (x1), HDMI-Out v2.0 (4K-UHD) (x1), AV-Out (x1), Audio-Out 3.5mm (x1), LAN (x1), RS232 (x1), USB A 2.0 (x4), USB A 3.0 (x2), USB B for Touch (x2)
Internal Speakers	12W (x2) (Stereo)	12W (x2) (Stereo)	12W (x2) (Stereo)	15W (x2) (Stereo)
Power Supply (Internal)	AC 100-240V, 50/60Hz			AC 100-240V, 50/60Hz. Consumption: 480W, <0.5W (Standby)
Dimensions	1,521 x 915 x 99 mm	1,762 x 1,034 x 101 mm	1,988 x 1,178 x 99.6 mm	2242 x 1338 x 117 mm
Weight (Net)	46 kg	60 kg	78 kg	138 kg
Weight (Gross)	60.4 kg	84.2 kg	111.2 kg	191 kg
Model UPC Code	813097023063	813097023056	813097023049	813097024329
Accessories (Standard)	AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control, Wall Mount Kit, Documentation Kit			Touch Screen Panel, NovoEnterprise NE3000EU, Wall Mount, Documentation Kit, AC Power Cord, HDMI Cable, USB Cable, Audio Cable, Stylus (x2), Remote Control with Batteries.