

	NovoDisplay DK430	NovoDisplay DK550	NovoDisplay DK650	NovoDisplay DK750	
<b>DISPLAY</b>	Technology	IPS Panel, Backlit LED	IPS Panel, Backlit LED	IPS Panel, Backlit LED	
	Panel Size	43"	55"	65"	
	Brightness	350 Nits			450 Nits
	Native Resolution	4K-UHD (3840 x 2160)			
	Aspect Ratio	16:9			
	Contrast Ratio	1,300:1			
	Viewing Angle (Horizontal/Vertical)	178°/178°			
	Refresh Rate	60 Hz			
	Color Processing	1.07 Billions			
	Orientation	Landscape			
<b>SYSTEM</b>	Operation System	Android™ v7.1			
	CPU	RK3399 ARM Cortex A72 and Quad Core ARM Cortex A53			
	GPU	Mali™- T860MP4			
	RAM	2GB DDR3			
	Internal Storage	16GB (eMMC Flash)			
<b>CONNECTIVITY</b>	BYOD Supported System	Windows 7 / 8 / 10 (32 bits and 64 bits), macOS 10.7 and above, Ubuntu, iOS 7.0 and above, Android 4.0 and above, Chromebook			
	Input	HDMI v2.0 (x2), DisplayPort v1.2 (x1), DVI-D (x1), VGA (x1), Audio-In Mini-Jack 3.5mm (x1), USB A 2.0 (x3), USB C (x1), microSD Slot, RS232 (x2)			
	Output	DVI-D (x1), Audio-Out Mini-Jack 3.5mm (x2), RS232 (x1)			
	Network	LAN (x1), Wifi 802.11ac,b/g/n 2.4GHz & 5GHz			
<b>FEATURES</b>	Collaboration	BYOD Wireless Screen Mirroring, Meeting ID, Customizable Meeting Room Name, QR Code Connection Support, Split Screen, Moderator, Customizable Welcome Screen, USB Multimedia Reader			
	Digital Signage Announcement Board	NovoDS Digital Signage - Message and Announcement Board, Intuitive Drag-and-Drop Interface, Flexible Playlist Creation, Dynamic Content from text, audio, photos and videos to webpages, Twitter, RSS, Google Calendar, Weather, and More			
<b>GENERAL</b>	Internal Speakers	5W (x2) (Stereo)	5W (x2) (Stereo)	8W (x2) (Stereo)	15W (x2) (Stereo)
	Power	Supply: AC 100-240V, 50/60Hz. Consumption: 85W, <0.5W (Standby)	Supply: AC 100-240V, 50/60Hz. Consumption: 140W, <0.5W (Standby)	Supply: AC 100-240V, 50/60Hz. Consumption: 170W, <0.5W (Standby)	Supply: AC 100-240V, 50/60Hz. Consumption: 400W, <0.5W (Standby)
	Operation Environment	Operating Temperature: 0°C - 40°C. Operating Humidity: 20% - 85% (No Condensation)			
	Storage Environment	Storage Temperature: -10°C - 60°C. Storage Humidity: 10% - 90% (No Condensation)			
	VESA	VESA 400 x 200	VESA 400 x 400	VESA 600 x 400	VESA 600 x 400
	Product Dimensions (L x H x W)	970 x 559 x 85 mm	1,244 x 714 x 70 mm	1,477 x 852 x 80 mm	1,715 x 993 x 93 mm
	Bezel Width (U / B / L / R)	13 mm	13,9 mm	23,1 mm	31,5 mm
	Weight (Net)	9 Kg	15 Kg	29 Kg	41 Kg
	What's Included	Flat Panel, OPS Module, Antennas, Wall Mount Kit, AC Power Cord, Remote Control with Batteries, Document Kit			
	Optional Accessory	LauncherPlus Type A, LauncherPlus Type C, LauncherOne			
<b>LOGISTICS</b>	Weight (Gross)	13 Kg	19 Kg	40 Kg	53 Kg
	Carton Dimensions (L x W x H)	1,070 x 153 x 633 mm	1,364 x 154 x 824 mm	1,660 x 245 x 1,045 mm	1,880 x 245 x 1,125 mm
	UPC	813097024657	813097024664	813097024671	813097024688